



Leaves nothing
to be desired!



AquaCat SUPER

AquaCat SUPER

The AquaCat SUPER lives up to its promise. No matter what the situation, the cleaner can cope with it. The SUPER even detects obstacles on its path and simply drives around them. The cleaner is suitable for all swimming pool shapes and surfaces up to 200 m². You can use the radio remote control for an individual control of the AquaCat SUPER and a systematic cleaning of certain areas. The electronic Gyro system prevents a twisting of the floating cable.

The Easy Filter Service (EFS) is a special highlight of the AquaCat SUPER. The reusable filter cartridges can be removed from the top with one hand, allowing an easy emptying and cleaning of the filters. The Easy Filter Service (EFS) is a special highlight.

Also in terms of quality, the SUPER sets a milestone. The new robust gear system replaces the former drive belts. This could be compared to a tire change that is no longer required.

Due to diverse other setting options and short cleaning intervals, the AquaCat SUPER is also interesting for hotel pools.



Your advantages at a glance:

- Also ideal for large pools
- Improved water quality
- Clean floor and wall surfaces
- Cleans the high-maintenance water line
- Fast and effective
- Considerably reduced labour
- Customised cleaning programs
- Undisturbed privacy
- Reduced load on your filter system
- Improved recirculation of pool water
- Reduced consumption of water treatment agents
- Auto detect: prevents getting stuck on obstacles
- The SUPER is almost maintenance-free
- Transport trolley included
- Technical advice and service from your specialist dealer
- Technology from the market leader



Convenient:
AquaControl box and radio remote control

| | |
|------------------------------|--|
| Art. no.: | 1510-671-05 |
| Delivery includes: | Suction robot, transport caddy with cable holder |
| For swimming pool surfaces: | up to 200 m² |
| Supply voltage: | 230V / AC 50-60Hz |
| Safety voltage in pool: | 24V DC |
| Power consumption: | 180 W |
| Suction capacity: | 16 m³/h |
| Length of floating cable: | 23 m |
| Program cycle: | 90, 120 or 150 min |
| Water temperature: | +13°C to max. +35°C |
| Max. immersion depth: | 4 m |
| Min. immersion depth: | 40 cm |
| Weight of unit incl. cable: | Approx. 13 kg |
| Engine protection: | yes |
| Electronic Swivel system: | yes |
| Easy-Filter-Service (EFS): | yes |
| Gyro system: | yes |
| Internal timer: | yes |
| External timer: | yes |
| Auto detect: | yes |
| Dimensions | |
| Device with transport caddy: | 85 x 50 x 96 cm (l x w x h) |
| Dimensions suction robot: | 40 x 44 x 38 cm (l x w x h) |
| Cleaning width: | 31 cm |



The Easy Filter Service makes emptying and cleaning of the filter fast and easy

dinotec GmbH
Water and Pool Technology
Spessartstr. 7
63477 Maintal/Germany
Phone: +49 (6109) 6011-0
Fax: +49 (6109) 6011-90
E-mail: mail@dinotec.de
www.dinotec.de
www.niedrig-energie-pool.de
www.PoolsForHotels.com