



dinotecNET+

The All-rounder



Modern pool and spa management.
 more flexibility | more economy | more safety

Simply enjoy the best water!

Control unit




Everything under control

The system housing with 5.7" coloured touch panel is the heart of the dinotecNET+; the entire pool technology is controlled from this center.

All processes and hygiene parameters are clearly and concisely prepared and displayed.



Bus line



Control via touch panel

The control of all technical components and the visualisation of processes is realised by the press of a finger.

If required, a second touch panel can be positioned at various locations, e.g. at the reception, the pool attendant's room or in the immediate vicinity of the pool. The display is also available in other sizes on request.



Modular design

A suitable module is integrated in the system housing for each function; the appropriate field devices are installed in the system.

Compatible devices



Combitrol IMPULS

Actuator for standard 6-way valves (Praher). Assembly directly on valve. Alternative: Besgo automatic backwash valves.



DeviceControl

Control unit for any type of AC consumers up to 2 kW.



MotorControl

Control unit for three-phase motors up to 4 kW with integrated connection for pneumatic buttons.



SpeedControl

Frequency inverter for invariable rotation speed control of three-phase motors up to max. 15 kW.

D E V I C E S T H A T C A N B E



Suitable for use in filters of different sizes in private pools.




E.g. massage nozzles, sample water pumps, dosage pumps, small UV systems, lighting etc.



E.g. three-phase circulation pumps, attractions or blowers.



E.g. circulation pumps, attractions or blowers.



Pneumatic DriveControl

Controller for pneumatic actuators.



LevelControl 2

Hydrostatic, continuous level measurement for open tanks.



Humidity Temperature Sensor


Sensor for room temperature and humidity. Calculates dew point and dew point deviation.




dinodos START LEVEL BUS

Peristaltic pump with wear-free stepper motor drive. With precisely controllable, 0-8.5 l/h dosing range. Measurement of the fluid level in the supply container and display in the dinotecNET+.

C O N N E C T E D



Suitable for all valve drives.



Safe and reliable measurement, also for salt or mineral water.

Safety

In case of failure, all important functions can be switched directly via the devices.

24 h service via dinoRemote

On request, dinotec also provides full-service for maintenance and servicing of systems. All functions are permanently monitored via the Internet. Required corrections are carried out immediately by dinotec.

options



Facility management system

The dinotecNET+ system can be combined with all established facility management systems via standardised interfaces. Central control, no need for additional control elements.



PC/Internet

The entire dinotecNET+ system can be serviced and updated via the Internet.



Water attractions

The modular technology can be extended at any time with planned or existing water attractions.



Future-proof

The modular design allows unlimited expandability. dinotecNET+ simply grows along with new investments, for example in pool technology or attractions.

dinotec know-how

All system components are developed, tested, built and customised by dinotec. The complete organisation of the swimming pool – from planning via consultancy, installation to maintenance – is carried out by skilled staff and partners.



Simply enjoy the best water!

> Ideal hygiene conditions

due to fully automatic control and regulation.

> Simpler

due to easy operation and central .

> More economical operation

due to modern measurement-control technology and precise dosing.

> Expandable and future-proof

due to a flexible, modular design and a broad range of devices for pool technology.

> Individually customisable

to any existing system and to projects of different scopes.

> Can be used worldwide

All modules operate with 24 V DC .

> Cost-efficient planning and installation


Additional switch cabinets and complex cabling are now a thing of the past.

> Low maintenance requirements

Fewer interfaces.


Remote maintenance and diagnostics via Web and telephone possible.

The All-rounder for an up-to-date control of swimming pools and whirlpools:
more flexibility | more economy | more safety



Rocco Forte Hotel Villa Kennedy, Frankfurt/Germany





Your dinotec specialist dealer:

*Background photo:
Water photo no. 1
Artist:
Thomas Kuhn*

dinotec GmbH
Water & Pool Technology
Philipp-Reis-Str. 28
61130 Nidderau/Germany
Phone: +49 (6187) 41379-0
Fax: +49 (6187) 41379-90
E-mail: mail@dinotec.de
www.dinotec.de
www.niedrig-energie-pool.de
www.Poolpflege.info

Subject to technical changes. Errors excepted. 01/2020

Simply enjoy the best water!